



<b>Overpressure limit</b>	Brass - Diaphragm	20 bar	<b>Operating temperature</b>	See the guide to selection of diaphragms / seals	<b>Standard protection level</b>	.95 Faston Connection 180° - IP00 * See the attachment caps and connectors
<b>Working pressure</b>	Brass - Diaphragm	10 bar	<b>Max Hysteresis</b>	Diaphragm version 15% of full scale value		

Select specifications for product coding

1.	<b>Setting Range</b>		<b>01</b> Diaphragm 0.5-2.5 Bar	<b>02</b> Diaphragm 2.5-4.5 Bar	<b>03</b> Diaphragm 4.5-7.0 Bar
2.	<b>Electrical Load</b>				<b>5</b> 48 V / 0,2 A
3.	<b>Electrical Condition</b>				<b>A</b> Normally Open
4.	<b>Housing Material</b>			<b>B</b> Knurled Brass	<b>E</b> Brass SW17
5.	<b>Seals</b>				<b>N</b> NBR
6.	<b>Threads (X1)</b>			<b>10</b> 1/8"BSPP L1 10 mm	<b>40</b> 1/8"- 27NPT L1 10 mm
7.	<b>Customizations</b> <small>* See the attachment caps and connectors</small>		<b>.95</b> Faston Connection 180° - IP00	<b>.F0</b> Faston Connection - IP00	<b>.96</b> Dual Cable L. 250mm - IP67

PR1

1.	2.	3.	4.	5.	6.	7.
----	----	----	----	----	----	----