


ELECTRICAL CONDITION



<b>Max Pressure</b>	250 bar	<b>Intervention Tolerance</b>	± 3,5	<b>Tightening Torque</b>	25 Nm
<b>Electrical Load Type</b>	48V / 1A 24V / 2A 250Vac / 1A	<b>Thermal Hysteresis</b>	< 5 °C	<b>Housing Material</b>	Brass Hex 24mm
<b>Fluid Temperature</b>	-40 ÷ +150 °C	<b>Standard Protection Level</b>	.96 Cable 2 x 0,75 - IP67	* See the attachment caps and connectors	

Select specifications for product coding

<p>↓</p> <p>1.</p> <p>2.</p> <p>3.</p> <p>4.</p> <p>5.</p> <p>6.</p> <p>7.</p> <p>↓</p>	<b>Threads (X1)</b>							<b>09</b>	<b>12</b>	<b>25</b>			
								1/2" BSPP L1 13,5 mm	3/8" BSPP L1 13,5 mm	M22x 1,5 L1 13,5 mm			
	<b>Switching Temperature</b>	<b>030</b>	<b>040</b>	<b>050</b>	<b>060</b>	<b>070</b>	<b>080</b>	<b>090</b>	<b>100</b>	<b>110</b>	<b>120</b>		
		30° C	40° C	50° C	60° C	70° C	80° C	90° C	100° C	110° C	120° C		
	<b>Electrical Condition</b>									<b>A</b>	<b>C</b>		
										Normally Open	Normally Closed		
	<b>Switching</b>									<b>S</b>	<b>D</b>		
									Rising Setup	Falling Setup			
<b>Probe Length (L2)</b>									<b>1</b>	<b>2</b>			
									Probe 15 mm	Probe 25,4 mm			
<b>Cable Type</b>									<b>F</b>	<b>C</b>			
									Flying Leads	Cable 2 x 0,75			
<b>Customizations</b>									<b>.96</b>	<b>.97</b>	<b>.98</b>	<b>.99</b>	<b>.XX</b>
									Cable 2 x 0,75 L. 250 mm - IP67	Cable L. 250mm Conn. AMP Superseal 1.5 2 vie -IP67	Cable L. 250 mm Conn. Deutsch DT04-2P - IP67	Cable L. 250 mm Conn. Metri-Pack (MP280) - IP67	Customized product

TF3

1.	2.	3.	4.	5.	6.	7.
----	----	----	----	----	----	----