


ELECTRICAL CONDITION



<b>Max Pressure</b>	250 bar	<b>Intervention Tolerance</b>	± 4	<b>Tightening Torque</b>	25 Nm
<b>Electrical Load Date</b>	12V / 30A 24V / 30A	<b>Thermal Hysteresis</b>	< 16 °C	<b>Housing Material</b>	Brass Hex 27mm
<b>Fluid Temperature</b>	-40 ÷ +120 °C			<b>Standard Protection Level</b>	.99 Cable L. 250 mm Metri-Pack Connector (MP280) - IP67 * See the attachment caps and connectors

Select specifications for product coding

↓	<b>1. Threads (X1)</b>								<b>09</b> 1/2" BSPP L1 13,5 mm	<b>12</b> 3/8" BSPP L1 13,5 mm	<b>25</b> M22x 1,5 L1 13,5 mm
	<b>2. Switching Temperature</b>	<b>030</b> 30° C	<b>040</b> 40° C	<b>050</b> 50° C	<b>060</b> 60° C	<b>070</b> 70° C	<b>080</b> 80° C	<b>090</b> 90° C	<b>100</b> 100° C	<b>110</b> 110° C	<b>120</b> 120° C
	<b>3. Electrical Condition</b>									<b>A</b> Normally Open	<b>C</b> Normally Closed
	<b>4. Switching</b>									<b>S</b> Rising Setup	<b>D</b> Falling Setup
	<b>5. Electrical Load Type</b>									<b>.12</b> 12V / 30A	<b>.24</b> 24V / 30A
	<b>6. Customizations</b> * See the attachment caps and connectors									<b>.99</b> Cable L. 250 mm Metri-Pack Connector (MP280) - IP67	<b>.XX</b> Customized Product

TRL

1.	2.	3.	4.	5.	6.
----	----	----	----	----	----