



<b>Max Pressure</b>	200 bar	<b>Fluid Temperature</b>	-20 ÷ +80 °C	<b>Housing Material</b>	Brass Hex 34mm
<b>Supply Voltage</b>	12÷24 Vdc	<b>Intervention Tolerance</b>	± 3,5	<b>Supply Cable</b>	1,00 m
<b>Max Load</b>	20 A	<b>Output Signal</b>	PWM	<b>Standard Protection Level</b>	Cable L. 250 mm Metri-Pack Conn. (MP280) - IP67 * See the attachment caps and connectors
		<b>Tightening Torque</b>	25 Nm		

### Select specifications for product coding

1.	<b>Threads (X1)</b>								<b>09</b> 1/2" BSPP L1 13,5 mm	<b>12</b> 3/8" BSPP L1 13,5 mm	<b>25</b> M22x 1,5 L1 13,5 mm
2.	<b>Switch-on Temperature (°C)</b>	<b>030</b> 30° C	<b>040</b> 40° C	<b>050</b> 50° C	<b>060</b> 60° C	<b>070</b> 70° C	<b>080</b> 80° C	<b>090</b> 90° C			
3.	<b>100% Output Power Temperature (°C)</b>	<b>030</b> 30° C	<b>040</b> 40° C	<b>050</b> 50° C	<b>060</b> 60° C	<b>070</b> 70° C	<b>080</b> 80° C	<b>090</b> 90° C			
4.	<b>Customizations</b> * See the attachment caps and connectors				<b>.97</b> Cable L. 250mm AMP Superseal Conn. 1.5 2 vie -IP67	<b>.98</b> Cable L. 250 mm Deutsch Conn. DT04-2P - IP67	<b>.99</b> Cable L. 250 mm Metri-Pack Conn. (MP280) - IP67	<b>.XX</b> Customized Product			

TS2

1.	2.	3.	4.
----	----	----	----