



Overpressure limit	Brass - Diaphragm Steel - Diaphragm	15 bar 15 bar	Operating temperature	* See the guide to selection of diaphragms / seals		Standard protection level	IP67 * See the attachment caps and connectors
Working pressure	Brass - Diaphragm Steel - Diaphragm	10 bar 10 bar	Max Hysteresis	Diaphragm conf.	10% of full scale value		

Select specifications for product coding

1.	Setting Range									01	02			
										Diaphragm -100 :-500	Diaphragm -500 :-900			
2.	Electrical Load									4	5			
										12V / 100mA Gold plated	250Vac / 5A 48Vdc / 4A			
3.	Electrical Condition									A	C			
										Normally Open	Normally Closed			
4.	Housing Material									B	Z	I	W	
										Brass	Galvanized Steel	Stainless Steel 303	Stainless Steel 316	
5.	Seals									H	E	S	V	I
										HNBR	EPDM	MVQ (silicone)	FKM	Stainless Steel Diaphragm
6.	Threads (X1)	00	01	10	11	20	21	23	40	41				
		1/8"BSPT L1 10 mm	1/4"BSPT L1 12 mm	1/8"BSPP L1 10 mm	1/4"BSPP L1 12 mm	M10x1 L1 10 mm	M10x1K L1 10 mm	M12x1.5 L1 12 mm	1/8"- 27NPT L1 10 mm	1/4" - 18NPT L1 12 mm				
7.	Customizations										.S0	.D0	.XX	
	* See the attachment caps and connectors										Conn. AMP Superseal 1.5 2 way - IP67	Conn. Deutsch DT04 2P - IP67	Customized product	
8.	Adjustable (bar)										S	D		
											Rising Setup	Falling Setup		

VR9

1.	2.	3.	4.	5.	6.	7.	8.
----	----	----	----	----	----	----	----